



www.limpidworld.com

4 CHANNEL DVR

Limpid Provides Trusted Security Solutions To The Global Market In Each Industry.

DVR MODEL
LW-DR-04R1N

 **SIGNATURE** Series

Product Casing And Specifications Are Subject To Change Without Prior Notice

FC CE RoHS     

4 CHANNEL DVR

DVR MODEL: LW-DR-04R1N



KEY FEATURES:

- H.264 4 channel 1080N
- Support VGA and HDMI output
- Maximum output bandwidth 16Mbps
- Support remote mobile surveillance
- Display support 1080N and IP realtime
- Record support 1080N and IP realtime
- Synchronous Playback 4CH
- Support PTZ RS485 control
- 1SATA HDD 6TB



DVR Features

Video Compression		H.264
Video System		NTSC/PAL
Operation System		Linux (Embedded)
Analog Video-Input/Output		4CH Inputs / VGA and HDMI Output
IP Video Input		2ch, (Only IP Up to 6ch)
Composite Video Input		Up to 6ch (Analog Video + IP Video)
Audio Input /Output		4CH Inputs /1CH Output(RCA)
Display	Resolution	Analog :1080N/720P/960H IP :1080P/720P
	Feature	1/4/6/S.E.Q.
Record	Resolution	Analog :1080N/720P/960H IP :1080P/720P
	Speed	Analog :1080N(960*1080):15fps(Each Ch) 720P:15fps(Each Ch) 960H:PAL:25fps(each ch)/NTSC:30fps(Each Ch) IP :PAL:25fps(each ch) / NTSC: 30fps(Each Ch)
IP-Recording Bandwidth (Maximum input Bandwidth)		8Mbps ~24Mbps(Default is 8Mbps, Decrease One Analog Channel Can Increase 4Mbps)
Maximum output Brandwidth		16Mbps
Recording Mode		Continuous/Manual/Motion Detect
Synchronous Playback		4CH

4 CHANNEL DVR

DVR MODEL: LW-DR-04R1N

DVR Features

Network Type	LAN, DHCP, And DDNS
HDD Interface	1SATA HDD, Up to 6TB
Multiplex Operation	Live Display, Record, Playback, Backup and Network
USB	2xUSB (For Mouse and Backup/Upgrade)
PTZ Control	Yes (RS485)
Mobile Surveillance	iPhone, Android
VGA/HDMI	1024*768,1280*1024,1440*900,1920*1080
Power Supply	DC 12V/2A
Dimension(WxDxH)	300X227X53mm
Working Temperature	-10°C~+55°C
Working Humidity	10%~90%