



www.limpidworld.com

8 CHANNEL DVR

Limpid Provides Trusted Security Solutions To The Global Market In Each Industry.

DVR MODEL
LW-DR-08R1N

 **SIGNATURE** Series

Product Casing And Specifications Are Subject To Change Without Prior Notice

FC CE RoHS 

8 CHANNEL DVR

DVR MODEL: LW-DR-08R1N



KEY FEATURES:

- H.264 8 CHANNEL 1080N
- Support VGA and HDMI Output
- Maximum Output Bandwidth 16Mbps
- Support Remote Mobile Surveillance
- Display Support 1080N and IP Realtime
- Record Support 1080N and IP Realtime
- Synchronous Playback 8CH
- Support PTZ RS485 control
- 1 SATA HDD 6TB



DVR Features

| | | |
|---------------------------------------------------------|-------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Video Compression | | H.264 |
| Video System | | NTSC/PAL |
| Operation System | | Linux (Embedded) |
| Analog Video-Input/Output | | 8CH Inputs / VGA and HDMI Output |
| IP Video Input | | 4ch, (Only IP Up to 12ch) |
| Composite Video Input | | Up to 12ch (Analog Video + IP Video) |
| Audio Input /Output | | 4CH Inputs /1CH Output(RCA) |
| Display | Resolution | Analog :1080N/720P/960H IP :1080P/720P |
| | Feature | 1/4/6/8/9/10/13/14/S.E.Q. |
| Record | Resolution | Analog :1080N/720P/960H IP :1080P/720P |
| | Speed | Analog :1080N(960*1080) :15fps(Each Ch) 720P:15fps(Each Ch) 960H:PAL:25fps(each ch)/NTSC:30fps(Each Ch) IP :PAL:25fps(each Ch) / NTSC: 30fps(Each Ch) |
| IP-Recording Bandwidth (Maximum input Bandwidth) | | 12Mbps ~36Mbps(default is 12Mbps, Decrease One Analog Channel Can Increase 4Mbps) |
| Maximum Output Bandwidth | | 16Mbps |
| Recording Mode | | Continuous/Manual/Motion Detect |
| Synchronous Playback | | 8CH |

8 CHANNEL DVR

DVR MODEL: LW-DR-08R1N

DVR Features

| | |
|----------------------------|----------------------------------------------------|
| Network Type | LAN, DHCP, And DDNS |
| HDD Interface | 1SATA HDD, Up to 6TB |
| Multiplex Operation | Live Display, Record, Playback, Backup and Network |
| USB | 2xUSB (For Mouse and Backup/Upgrade) |
| PTZ Control | Yes (RS485) |
| Mobile Surveillance | iPhone, Android |
| VGA/HDMI | 1024*768,1280*1024,1440*900,1920*1080 |
| Power Supply | DC 12V/2A |
| Dimension(WxDxH) | 300X227X53mm |
| Working Temperature | -10°C~+55°C |
| Working Humidity | 10%~90% |