



www.limpidworld.com

16 CHANNEL DVR

Limpid Provides Trusted Security Solutions To The Global Market In Each Industry.

DVR MODEL
LW-DR-16R2P

 **SIGNATURE** Series

Product Casing And Specifications Are Subject To Change Without Prior Notice

FC CE RoHS     

16 CHANNEL DVR

DVR MODEL: LW-DR-16R2P



KEY FEATURES:

- H.264 16 CHANNEL 1080P
- Support VGA and HDMI output
- Maximum Output Bandwidth 64Mbps
- Support Remote Mobile Surveillance
- Display 3MP 18fps, IP up to 4MP
- Record 3MP 12fps, IP full frames
- Synchronous Playback 16CH
- Support Sensor & Alarm I/O
- Support PTZ RS485 control
- 2 SATA HDD 12TB

16CH

H.264
COMPRESSION

CMS

ALARM

1080N

SMART PHONE

2 SATA

DVR Features

Video Compression		H.264
Video System		NTSC/PAL
Operation System		Linux (Embedded)
Analog Video-Input/Output		16CH Inputs / VGA and HDMI Output
IP Video Input		8ch, (Only IP Up to 24CH)
Composite Video Input		Up to 24CH (Analog Video + IP Video)
Audio Input /Output		16CH Inputs /1CH Output(RCA)
Display	Resolution	Analog : 3MP(18fps) 1080P/720P/960H IP : 4MP/3MP1080P/720P
	Feature	1/4/6/8/9/10/13/14/16/17/19/22/25/S.E.Q.
Record	Resolution	Analog : 3MP/1080P/720P/960H IP : 4MP/3MP1080P/720P
	Speed	Analog : 3MP:12fps(Each Ch) 1080P:PAL:15fps(Each Ch) 720P:PAL:25fps(Each Ch)/NTSC::30fps(Each Ch) 960H:PAL:25fps(Each Ch)/NTSC::30fps(Each Ch) IP : PAL:25fps(Each Ch)/NTSC: 30fps(Each Ch)
IP-Recording Bandwidth (Maximum input Bandwidth)		32Mbps ~96Mbps(default is 32Mbps, Decrease One Analog Channel Can Increase 4Mbps)
Maximum Output Brandwidth		64Mbps
Recording Mode		Continuous/Manual/Motion Detect
Sensor & Alarm I/O		16 Inputs /1 Output

16 CHANNEL DVR

DVR MODEL: LW-DR-16R2P

DVR Features

PTZ Control	Yes (RS485)
Mobile Surveillance	iPhone, Android
Synchronous Playback	16 CHANNEL
Network Type	LAN, DHCP, and DDNS
HDD Interface	2 SATA HDDs, Up to 12TB
Multiplex Operation	Live Display, Record, Playback, Backup and Network
USB	2xUSB (For Mouse and Backup/Upgrade)
VGA/HDMI	1024*768, 1280*1024, 1440*900, 1280*720, 1920*1080 , 1680*1050 1600*1200, 1920*1200, 2560*1440 3840*2160
Power Supply	DC 12V/5A
Dimension(WxDxH)	378x340x50mm
Working Temperature	-10°C~+55°C
Working Humidity	10%~90%