



[www.limpidworld.com](http://www.limpidworld.com)

# 32 CHANNEL DVR

Limpid Provides Trusted Security Solutions To The Global Market In Each Industry.

DVR MODEL  
**LW-DR-32R2P**

 **SIGNATURE** Series

Product Casing And Specifications Are Subject To Change Without Prior Notice

FC CE RoHS     

# 32 CHANNEL DVR

**DVR MODEL: LW-DR-32R2P**



### KEY FEATURES:

- H.264 32 CHANNEL 1080P
- Support VGA and HDMI output
- Maximum Output Bandwidth 128Mbps
- Support Remote Mobile Surveillance
- Display 3MP 18fps, IP up to 4MP
- Record 3MP 8fps, IP Full Frames
- Synchronous Playback 16CH
- Support Sensor & Alarm I/O
- Support PTZ RS485 Control
- 2 SATA HDD12TB

**32CH**

**H.264**  
COMPRESSION

**CMS**

**ALARM**

**1080N**

**SMART PHONE**

**2 SATA**

**SIGNATURE Series**

### DVR Features

<b>Video Compression</b>		H.264
<b>Video System</b>		NTSC/PAL
<b>Operation System</b>		Linux (Embedded)
<b>Analog Video-Input/Output</b>		32CH inputs / VGA and HDMI output
<b>IP Video Input</b>		8CH
<b>Composite Video Input</b>		Up to 40CH (Analog Video + IP Video)
<b>Audio Input /Output</b>		4CH Inputs /1CH Output(RCA)
<b>Display</b>	<b>Resolution</b>	Analog : 3MP(18fps) 1080P/720P/960H IP : 4MP/3MP1080P/720P
	<b>Feature</b>	1/4/6/8/9/10/13/14/16/17/19/22/25/32/36/49/S.E.Q.
<b>Record</b>	<b>Resolution</b>	Analog : 3MP/1080P/720P/960H IP : 4MP/3MP1080P/720P
	<b>Speed</b>	Analog : 3MP:8Fps(Each CH) 1080P:PAL:15Fps(Each CH) 720P:PAL:25Fps(Each CH) /NTSC::30Fps(Each CH) 960H:PAL:25Fps(Each CH) /NTSC::30Fps(Each CH) IP : PAL:25Fps(Each CH)/NTSC: 30Fps(Each CH)
<b>IP-Recording Bandwidth (Maximum input Bandwidth)</b>		32Mbps
<b>Maximum Output Brandwidth</b>		128Mbps
<b>Recording Mode</b>		Continuous/Manual/Motion Detect
<b>Synchronous Playback</b>		16CH

## 32 CHANNEL DVR

DVR MODEL: LW-DR-32R2P

### DVR Features

<b>Network Type</b>	LAN, DHCP, and DDNS
<b>HDD Interface</b>	2 SATA HDDs, Up to 12TB
<b>Multiplex Operation</b>	Live Display, Record, Playback, Backup and Network
<b>USB</b>	2xUSB (For Mouse and Backup/Upgrade)
<b>Sensor &amp; Alarm I/O</b>	YES- 8CH Inputs /1CH Output
<b>PTZ Control</b>	YES (RS485)
<b>Mobile Surveillance</b>	iPhone, Android
<b>VGA/HDMI</b>	1024*768, 1280*1024, 1440*900, 1280*720 1920*1080, 1680*1050, 1600*1200, 1920*1200 2560*1440, 3840*2160
<b>Power Supply</b>	DC 12V/5A
<b>Dimension (WxDxH)</b>	378x340x50mm
<b>Working Temperature</b>	-10°C~+55°C
<b>Working Humidity</b>	10%~90%